CROSS PINNACLE

SERIES **FCP1400HD**

TYPE **IAA**

FIBERGLASS **PLATFORM TO LEANING LADDER**

375 LBS
LOAD CAPACITY
(Includes weight of user plus materials)

2 IN 1 PLATFORM LADDER

USE LADDER AS A **PLATFORM** AND **LEANING** LADDER



LARGE SLIP RESISTANT PLATFORM WITH BUILT IN OVERFLOW SLOTS

WORK FACING MULTIPLE DIRECTIONS

It is not recommended that worker face ladder steps while on platform

COMPATIBLE WITH PINNACLE GATE ACCESSORY

Installing the Pinnacle Gate accessory allows 4 sided contact, permitting 360° of working access.

ANSI
Meets or exceeds requirements of American National Standards Institute
ANSI A14.5

MEETS OSHA REQUIREMENTS

LOUISVILLE LADDER

BECAUSE **WORK AIN'T PLAY.**

CROSS PINNACLE

SERIES FCP1400HD

1 ProTop™

The V-shaped Pro Top™ leans on walls, poles, and onto and into corners. The integrated bumper protects the working surface while the top provides multiple tool slots and tool tether anchor attachment points.

2 Larger Platform

Overflow slots keep materials from building up on the surface. Slip-resistant tread on this spacious platform allows for secure work and comfortable movement.

3 Extended Handrail

36" heavy-duty handrail runs from platform to peak providing a secure 3-sided barrier.

*Works with Pinnacle Gate Accessory to allow for 360º work access.

4 Raptor Boot™

Polypropylene copolymer upper boot and thick, non-marring thermoplastic elastomer tread deliver maximum protection for your ladder and its cargo.

5 SHOX™

Advanced impact absorption system offers superior protection against damage.

MODEL	PLATFORM HEIGHT	BOTTOM WIDTH (IN)	APPROX. SPREAD (IN)	APPROX. WEIGHT (LBS)	APPROX. CUBES (FT)	HIGHEST STANDING LEVEL (IN)	MAX. REACH
FCP1402HD	1′ 11″	21 15/16	30 ¼	25	8.8	1'11"	8'6"
FCP1403HD	2' 10″	23 15/16	35 ½	30	11.4	2' 10"	9'5"
FCP1404HD	3′ 10″	25 7/16	41 ¼	34	14.1	3′ 10″	10'5"
FCP1406HD	5′ 8″	28 ⅜	54	43	20.1	5′ 8″	12'3"
FCP1408HD	7′ 7″	31 ⅝	66	52	27.2	7′ 7″	14'2"

LOUISVILLE LADDER

LOUISVILLELADDER.COM

1.800.666.2811