



# PORTABLE MAGNETIC DRILLS

		HMD130	HMD900	HMD904	HMD905	HMD906	HMD927	HMD2MT	HMD920	HMD918	HMD934
		Low Profile	Fabricating					Heavy Duty Drilling			
Cutters	RotaLoc Plus™	✓	With Adapter	With Adapter	With Adapter	With Adapter	With Adapter	With Adapter	With Adapter	With Adapter	
	"12,000-Series"		✓	✓	✓	✓	✓	✓	✓	✓	✓
	Copperhead™ Carbide Tipped		✓	✓	✓	✓	✓	✓	✓	✓	
Model Specifications	Diameter Min./Max.	7/16" to 1-3/8" (12 - 35mm)	7/16" to 1-1/2" (12 - 38mm)	7/16" to 1-1/2" (12 - 38mm)	7/16" to 2" (12 - 50mm)	7/16" to 2" (12 - 50mm)	7/16" to 1-5/8" (12 - 41mm)	7/16" to 1-5/8" (12 - 41mm)	7/16" to 2-3/8" (12 - 60mm)	7/16" to 2-3/8" (12 - 60mm)	5/8" to 3-1/16" (16 - 77mm)
	Depth Max.	1" (25mm)	2" (50mm)	2" (50mm)	2" (50mm)	2" (50mm)	2" (50mm)	2" (50mm)	3" (76mm)	6" (152mm)	4" (100mm)
	Cutter Mounting	Bayonet Style	3/4" Double Flat	3/4" Double Flat	3/4" Double Flat	3/4" Double Flat or Fusion2™	3/4" Double Flat	3/4" Double Flat	3/4" Double Flat	3/4" Double Flat	3/4" Double Flat
	No-Load R.P.M.	450	450	450	250 / 450	350 / 650	250 / 450	250 / 450	250 / 450 / 700	250 / 450	70 / 120 / 200 / 332
	Model Weight	23.8 lbs (10.8 kg)	27.7 lbs (12.6 kg)	30 lbs (13.6 kg)	35 lbs (15.9 kg)	35 lbs (15.9 kg)	43 lbs (19.5 kg)	40.2 lbs (18.1 kg)	49 lbs (22.2 kg)	44.2 lbs (20.1 kg)	72 lbs (32.6 kg)
	Thru-the-Tool Coolant			✓	✓	✓	✓	✓	✓	✓	✓
	Carrying Case Included	✓		✓	✓	✓		✓	✓	✓	
Available Accessories	Swivel Base			Optional	Optional	Optional	Optional		Optional		
	#2 Morse Taper							✓	With Adapter	With Adapter	
	Pipe Adapter		✓	✓	✓	✓	Manual Mode	✓	✓	✓	
	Tap Attachment			✓	✓	✓	Manual Mode	✓	✓	✓	
	Vac-Pad™		✓	✓	✓	✓					
	Coolant Bottle			Optional	Included	Included	Included	Included	Included	Pressurized	Included
	Countersink Kit		✓	✓	✓	✓	Manual Mode	✓	✓	✓	✓
	Twist Drill Adapter		✓	✓	✓	✓	Manual Mode	✓	✓	✓	✓
	Ratchet Drive	✓		✓	✓	✓		✓	✓	✓	
	Arbor Extender		✓	✓	✓	✓	Manual Mode	✓	✓	✓	✓
	Drill Chuck		✓	✓	✓	✓	Manual Mode	✓	✓	✓	
	RotaLoc™ Spindle Adapter		✓	✓	✓	✓	Manual Mode	✓	✓	✓	